ITU - Telecommunication Standardization Sector

Temporary Document RN-091

STUDY GROUP 15

Original: English

Red Bank, New Jersey, 21 - 25 May 2001

Question: 4/15

SOURCE¹: VOCAL Technologies Ltd. (http://www.vocal.com)

TITLE: G.gen.bis: G.dmt.bis: G.lite.bis: G.vdsl: About the use of a fix interleaver size in Turbo Coding for high order constellations.

ABSTRACT

This contribution discuss the use of a fix interleaver size with high order constellations. The constellation used to illustrate the results is a b=14 bits constellation with 12 information bits and 2 parity bits.

<u>1.</u> Introduction

This contribution discuss the use of a fix interleaver size with high order constellations. The constellation used to illustrate the results is a b=14 bits constellation with 12 information bits and 2 parity bits.

2. Simulation Results

Figure 1 shows the simulation results for a 14 bits constellation size with 12 information bits and 2 parity bits with an S-type interleaver size of 1088 bits and with a S-type interleaver size of 31200 bits using 8 iterations.

Form the figure it is clear that the 1088 bits interleaver size does not perform well with high order constellations.

¹ Contact: Alberto Torres, Ph. D. Victor Demjanenko, Ph. D. Frederic Hirzel VOCAL Technologies Ltd.

E: jatorres@vocal.com E: victord@vocal.com E: frederich@vocal.com T: +1-716-688-4675 F: +1-716-639-0713



BER Rate 12/14 16384QAM N=1088 bits and N=31200 bits S-type interleaver and AWGN Channel

Figure 1. BER for rate 12/14 16384 QAM in AWGN channel

3. Summary:

This contribution discuss the problems that occur when a fix interleaver size of 1,088 is used with high order constellations. The constellation used to illustrate the results is a b=14 bits constellation with 12 information bits and 2 parity bits.

- 1. Agenda Item: G.992.1.bis issue 4.6 and G.992.2.bis issue 10.14. G.vdsl issue 11.17
- 2. Expectations: The committee accepts the use of an interleaver size for Turbo codes of an integral number of DMT symbols.